

## CALIPB-BIVF-30(P)

[www.black.honeywell.com](http://www.black.honeywell.com)

### 2 Megapixel High Definition TDN IR IP Bullet Camera with Vari-focal Lens

#### High Performance IP Camera at an Economical Price

Assembled with a built-in 2.8~12mm vari-focal lens, Honeywell Black™ CALIPB-BIVF-30(P) is a weather-proof IP bullet camera designed for small-scale surveillance application. Equipped with 2 Megapixel (1920H x 1080V) sensor, the camera delivers 1080P high resolution image at @25fps. The IP66 weather-proof housing makes it suitable for installation in harsh outdoor areas.

#### Advanced Features

Featuring True Day/Night with IR-cut filter and built-in IR led, the camera can automatically switch to black and white in pitch black conditions and also gives an IR beam distance of up to 40 meters, providing superior images at both day and night time.

The CALIPB-BIVF-30(P) comes with a free CMS software CAL-CMS200 which provides rich functions such as video management, user management, storage, video output, etc. It's also compatible with the free mobile App software CALNVRView, which makes it easy to remotely access the NVR through any of the supported mobile devices including iPhone, iPad, or Android Smartphone.

#### Market Opportunities

Assembled with a built-in 2.8~12mm vari-focal lens, Honeywell Black™ CALIPB-BIVF-30(P) is designed for small surveillance application at very budget-friendly price. Featuring 2 megapixel (1920H x 1080V) sensor, 1080P high resolution image, TDN function, up to 40 meters IR night vision and optional PoE function, it is ideal for hotels, chain stores, commercial offices, hospitals, residential areas, warehouse, and education facilities and so on.

#### FEATURES

- 2 Megapixel (1920H x 1080V), 1080P HD resolution
- Main-profile H.264 compression, support dual-stream
- 1080P real-time video output
- 2.8mm~12mm vari-focal lens
- IR beam distance: 30~40m
- True Day / Night with automatic removable IR cut filter, DWDR
- Minimum illumination: Color: 0.01Lux, Black / White: 0.001 Lux (0 Lux: IR On)
- Motion detection, Privacy Masking, Mirror, Flip, Anti-flicker
- IP66 weather-proof
- Power: DC12V (CALIPB-BIVF-30), DC12V/PoE(CALIPB-BIVF-30(P))
- ONVIF Compliant
- Free CAL-CMS200 central management software compatible
- CALNVRView: free Android and Apple app give you full access to your surveillance system anytime, anywhere



## CALIPB-BIVF-30(P)

www.black.honeywell.com

### 2 Megapixel High Definition TDN IR IP Bullet Camera with Vari-focal Lens

#### SPECIFICATIONS

Model	CALIPB-BIVF-30	CALIPB-BIVF-30(P)
Image Sensor	1/2.8" CMOS	
Effective Pixels	1920 x 1080	
Minimum Illumination	Color: 0.01Lux @ (F1.2,AGC ON), 0 Lux (IR ON) B/W: 0.001 Lux @ (F1.2,AGC ON), 0 Lux (IR ON)	
Shutter Speed	Auto, 1/50 (1/60)s, 1/120s, 1/250s, 1/500s, 1/1000s, 1/2000s, 1/4000s, 1/10,000s (millisecond adjustable)	
Lens	Megapixel 2.8-12mm vari-focal lens	
IR Beam Distance	30-40m	
Day & Night	TDN, IR cut removable	
DWDR	ON/OFF	
Auto Gain Control	ON/OFF, 0~100 adjustable	
Slow Shutter	None, Low, Medium, High	
NT Level (DNR)	Day / Night 0~5 adjustable	
Image Set	Brightness, Contrast, Saturation, Hue can be customized through CMS client and IE browser	
OSD Display	Time title, Channel title	
<b>Image &amp; Compression</b>		
Video Compression	H.264 dual-stream	
Image Resolution & Frame Rate	Main Stream: 50Hz: 25fps (1920 x 1080), (1280 x 720) 60Hz: 30fps (920 x 1080), (1280 x 720) Sub Stream: 50Hz: 25fps (D1: 704 x 576), (CIF: 352 x 288) 60Hz: 30fps (D1: 704 x 480), (CIF: 352 x 2440)	
Bite Rate	32Kbps~8Mbps (H.264), Image resolution lowest / lower / general / high / higher / highest selectable	
Bite Rate Type	CBR / VBR	
Audio Compression	G.711a	
Watermark	ON/OFF	
<b>Network</b>		
Network Interface Protocol	ONVIF 2.0	
Support Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP (HTTPS, SIP, 802.1x, IPv6)	
Browser	IE6.0 to IE11.0	
Alarm Trigger	Video motion, video blind, video loss, device disconnect	
Motion Detection	396 zones	
Privacy Masking (Region Cover)	4 zones	
Max. User Access	5 users	
General Functions	Anti-flicker, dual stream, heartbeat, password protection	
<b>Interface</b>		
Ethernet	1 RJ45 10M / 100M self adaptive Ethernet interface	
Audio Interface	1 CH RCA Audio input	
Storage	Network Storage	
<b>Software</b>		
CMS	CAL-CMS200	
Mobile View APP	CALNVRView for iPhone, iPad, Android	
<b>Others</b>		
Operating Temperature	-10°C~60°C	
Operating Humidity	Less than 90% ( non-condensing)	

## CALIPB-BIVF-30(P)


www.black.honeywell.com

### 2 Megapixel High Definition TDN IR IP Bullet Camera with Vari-focal Lens

Model	CALIPB-BIVF-30	CALIPB-BIVF-30(P)
Power Supply	DC12V±10%	DC12V±10%, PoE
Power over Ethernet (PoE)	N/A	EEE 802.3af
Dimension	280mm x 101.5mm x 88mm	
Weight	660g	
IP Protection	IP66	
Certificate	CE, FCC, C-tick	

Note: Honeywell reserves the right, without notification, to make changes in product design and/or specifications.

### DIMENSION



### ORDERING

CALIPB-BIVF-30	Weather-proof IR Bullet Camera, 2 Megapixel, 1/2.8" CMOS, 1080P 25fps, TDN, IR beam distance: 30~40M, 2.8~12mm vari-focal lens, IP66, 12DVC, ONVIF
CALIPB-BIVF-30P	Weather-proof IR Bullet Camera, 2 Megapixel, 1/2.8" CMOS, 1080P 25fps, TDN, IR beam distance: 30~40M, 2.8~12mm vari-focal lens, IP66, 12DVC, PoE, ONVIF

For more information:

Security East Asia  
 Security Pacific  
 Security India  
 Security Middle East & N.Africa  
 Security Russia  
 Security China  
 Security Korea

Tel: (852) 2405 2323  
 Tel: 1300 234 234  
 Tel: (91) 124 4975000  
 Tel: (971) 4454 1704  
 Tel: (7) 495 7979371  
 Tel: (86) 400 8800 330  
 Tel: (82) 2799 6114

www.black.honeywell.com  
 security.black@honeywell.com

Honeywell Security Group  
 Automation & Control Solutions  
 Honeywell International Inc.  
 www.security.honeywell.com



May 2015  
 © 2015 Honeywell International Inc.